

INOVANCE

ITS7000 Series HMI

New generation general purpose, easy integration for industry control system



- Dual-core / Quad-core processor
- IP66 rating (front side)
- 7" & 10.1" & 15.6" display sizes
- Built-in Ethernet and serial ports
- Type-C debug port
- Fastest boot time in 8 seconds, 50% less than last generation



EtherNet/IP™



OPC UA



Functions & Features



Functionality

- Supports VNC remote access through mobile devices 
- Trend chart & oscilloscope for continuous wave sampling
- Multi-language capability
- Support value alarm, deviation alarm, range alarm, etc.
- Alarm can be pushed by email



Graphical capabilities

- Up to 1024*600 resolution on 7" model (24 bit colours)
- Customizable user interface



Flexible connectivity

- Serial port and/or Ethernet standalone and multi-device networking
- Supports products from a wide range of 3rd party manufacturers
- Support for OPC UA, EtherNet/IP and Modbus RTU/TCP protocols



- IIoT ready:
MQTT implementation, seamlessly connects to any server



Programming

- User friendly **InoTouchPad** PC configuration software (Windows 11 compatible)



- Javascript and Canvas control for free graphic drawing
- Dedicated communication protocols, & access to external databases





Data management

- **Type-C** port for easy data management
- Maintains comprehensive historical data records
- Support U-disk storage, up to 5 million data records



Easy PLC adaption

- Exclusive tag communication, automatic synchronization
- Axis control and IO control combination binding
- Supports online & offline co-simulation
- Communication with RS485 specified cable
- Type-C port for program upload/download




Ordering code

ITS7 070 E H - G - INT
 ① ② ③ ④ ⑤ ⑥

<p>① Product series ITS: ITS7000 series HMI</p>	<p>④ Resolution None: Standard resolution H: High resolution</p>
<p>② Display size 070: 7" 100: 10.1" 156: 15.6"</p>	<p>⑤ Cover colour G: Light grey None: Dark grey (default)</p>
<p>③ Configuration S: Standard E: Enhanced P: Professional</p>	<p>⑥ Version: INT: International variant</p>


Terminals

ITS7070 / ITS7100



Note: [1]1-No Ethernet port on ITS7070S.
 [2] ITS7070 variants don't support.


ITS7156



Specifications

Model	ITS7070S-INT	ITS7070SH-INT	ITS7070E-INT	ITS7070EH-INT	ITS7100P-INT	ITS7156E-INT
	ITS7070S-G-INT	ITS7070SH-G-INT	ITS7070E-G-INT	ITS7070EH-G-INT	ITS7100P-G-INT	
Display size	7.0"				10.1"	15.6"
Resolution	800×480	1024×600	800×480	1024×600	1024×600	1920×1080
Brightness	350cd/m ²	400cd/m ²	350cd/m ²	400cd/m ²	350cd/m ²	250cd/m ²
Display colour	24-bit true colour					
Backlight	LED					
Display type	Landscape / portrait					
Backlight service life	35000H	25000H	35000H	25000H	30000H	30000H
CPU	Dual-core Cortex-A7				Quad-core Cortex-A7	Quad-core Cortex-A7
DRAM	128MB				256MB	512M
Flash	128MB				256MB	8GB
Ethernet interface	/		1		1	1
Serial port	COM1 (RS485/RS422) COM2 (RS232)		COM1 (RS485/RS422) COM2 (RS232) COM3 (RS485)		COM1(RS485/RS422) COM2 (RS232) COM3 (RS485)	COM1 DB9 (RS422/RS485) COM2 DB9 (RS232) COM3 DB9 (RS485)
USB type-C					1	
USB type-A					1	
SD card interface	x				✓	✓
Power	· Input voltage: 24V DC, scope of work 9V DC~28V DC · Rated input current: 360mA				· Input voltage: 24V DC, scope of work 9V DC~28V DC · Rated input current: 450mA	· Input voltage: 24V DC ±20% · Rated input current: 600mA
Dimensions (mm)	203×149×33				271×213×33	395×258×28.3
Weight	0.55kg				1.1kg	2kg
IP rating	Front side IP66, back cover IP20					
RTC	✓					

Example system architecture



Applications

Discrete Manufacturing Markets

HVAC | Water Pump Systems | CNC Machining Tools

Advantages



Up to 400cd/cm² luminance




Javascript supported



Million-level data records

Value

- Guaranteed stable performance in most normal conditions
- Edge computing accelerates local data processing
- With secure and reliable analytics



Motion Control Solution

Packaging Machinery-Single-Packaging Unit Applications

Value

- Modulized programming accelerates development by 40%
- Smart OEE analytics streamlines debugging
- 40% higher equipment productivity

Advantages



Tag access communication




Standardized template



Statistical report generation





- Inovance Worldwide
- Distribution & Service Partners

Advancing industrial technology, for a better world

www.inovance.eu
Enquires: info@inovance.ind.in

Shenzhen Inovance Technology Co., Ltd.
Suzhou Inovance Technology Co. Ltd.

☎ 4000-300124
✉ info@inovance.com
✉ service@inovance.com

Hong Kong SAR
International Export Office

☎ +852 2751 6080
✉ info@inovance.eu

INOVANCE

FOLLOW US



Germany-Stuttgart

☎ +49 (0) 7144 8990
✉ sales.de@inovance.eu

France-Bordeaux

☎ +33 (0) 5594 01050
✉ sales.fr@inovance.eu

Spain-Barcelona

☎ +34 93 504 94 48
✉ sales.es@inovance.eu

Italy-Milano

☎ +39 (0) 2268 22318
✉ sales.it@inovance.eu

Turkey-Istanbul

☎ +90 (216) 466 7600
✉ sales.tr@inovance.eu

South Korea-Seoul

☎ +82 (0) 10 7428 5732
✉ sales.kr@inovance.eu

India

☎ Head Office Chennai | +91 (0) 44 4380 0201
Ahmedabad | +91 (0) 79 40034274
Mumbai | +91 (0) 22 4516 6255
Noida | +91 (0) 120 402 8235
Hyderabad | +91 (0) 40 4951 6431
Surat | +91 93846 65692

Sales Network
Kolkata, Bengaluru, Pune, Coimbatore, Visakhapatnam, Vadodara, Jaipur
✉ info@inovance.ind.in