

# INOVANCE

## MD800 - Compact AC MultiDrive

Comprehensive functionality in a compact footprint



- Modular design (from 1 to 8 drives)
- 1/3 ph 200 V and 3 ph 400 V supply
- Drive ratings: 200 W to 11 kW
- STO SIL3
- Choice of fieldbus protocols available



reddot winner 2021  
innovative product



# MD800 – features & functions

## Comprehensive functionality:

- Individual STO SIL 3 for each drive
- Suitable for open loop asynchronous & PM synchronous motors
- +24 VDC control backup supply
- IP40 rated
- Remote LCD keypad (optional)
- Commissioning PC software available
- Dual rated: heavy duty (HD, G rating): 150% overload; normal duty (ND, P rating): 110% overload

## High level, flexible connectivity:

- Built-in I/Os: 4 DI, 4 DI/DO, 2 AI, 1 RO
- Standard onboard communications: USB commissioning port, CAN, RS485



- Two expansion slots
  - I/O expansion cards
  - Fieldbus option cards:

EtherCAT<sup>®</sup> EtherNet/IP<sup>™</sup>



## Reduced installation costs

- User-friendly pluggable connectors (spring type)
- Faster build time
- Reduced wiring
- User-friendly pluggable connectors (spring type)
- Fewer external components:
  - > Common EMC filter (C2 compliant)
  - > Input reactor
  - > Fuses/MCCBs
  - > Common built-in dynamic braking (variant)


## Compact footprint for smaller cabinets

- Common height and depth: 182 mm x 160 mm
- Rectifier width: 99.5 mm
- Drive width: 49.5 mm

## Designed for durability:


- High level conformal coating (3C3 & 3S2)
- Operating temp range: -20 to +60°C (de-rating > 50°C)
- Operating altitude: up to 4,000 m (de-rating > 1,000 m)
- Separate cooling channel for heatsink

This image is illustrated in its actual size: W 300 mm x H 182 mm




## Designed for cabinet space saving - reduced installation costs

Eight Inovance MD200 drives, each module's footprint is: W 75 mm x H 180 mm



Footprint reduction  
**-50%**



### Single drive units

Power (kW)		Part number	Model	Output AC current (A)		STO function
HD	ND			HD	ND	
400 V, DC supply voltage: 510-720 VDC						
0.4	0.75	0101B470	MD800-1-4T1R8	1.8	2.1	No
0.75	1.5	01019513	MD800-1-4T3R4	3.4	4.6	
1.5	2.2	0101B471	MD800-1-4T4R8	4.8	5.4	
2.2	3.7	01019514	MD800-1-4T5R5	5.5	9	
3.7	5.5	0101B472	MD800-1-4T9R5	9.5	13	
5.5	7.5	01019512	MD800-1-4T13	13	17	
7.5	11	01019506	MD800-1-4T17	17	21	
0.4	0.75	0101B582	MD800-1-4T1R8S	1.8	2.1	
0.75	1.5	0101B583	MD800-1-4T3R4S	3.4	4.6	
1.5	2.2	0101B586	MD800-1-4T4R8S	4.8	5.4	
2.2	3.7	0101B587	MD800-1-4T5R5S	5.5	9	
3.7	5.5	0101B590	MD800-1-4T9R5S	9.5	13	
5.5	7.5	0101B591	MD800-1-4T13S	13	17	
7.5	11	0101B555	MD800-1-4T17S	17	21	
200 V, DC supply voltage: 270-360 VDC						
0.2	0.4	0101BA93	MD800-1-2T1R7	1.7	1.9	No
0.4	0.75	0101BA92	MD800-1-2T3	3	3.5	
0.75	1.5	0101BA91	MD800-1-2T5	5	8	
1.5	2.2	0101BA89	MD800-1-2T8	8	9.6	
2.2	3.7	0101BA88	MD800-1-2T11	11	17.6	
3.7	5.5	0101CE51	MD800-1-2T17	17	21	
3.7	5.5	0101CD92	MD800-1-2T17S	17	21	
0.2	0.4	0101BD16	MD800-1-2T1R7S	1.7	1.9	
0.4	0.75	0101BA90	MD800-1-2T3S	3	3.5	
0.75	1.5	0101B584	MD800-1-2T5S	5	8	
1.5	2.2	0101BD17	MD800-1-2T8S	8	9.6	
2.2	3.7	0101BA94	MD800-1-2T11S	11	17.6	
3.7	5.5	0101BA87	MD800-1-2T17S	17	21	

### Dual drive units

Power (kW)		Part number	Model	Output AC current (A)		STO function	
HD	ND			HD	ND		
400 V, DC supply voltage: 510-720 VDC							
0.4	0.75	0101B469	MD800-2-4T1R8	1.8	2.1	No	
0.75	1.5	01019509	MD800-2-4T3R4	3.4	4.6		
1.5	2.2	0101AK33	MD800-2-4T4R8	4.8	5.4		
2.2	3.7	01019510	MD800-2-4T5R5	5.5	9		
3.7	5.5	01019511	MD800-2-4T9R5	9.5	13		
0.4	0.75	0101B576	MD800-2-4T1R8S	1.8	2.1		Yes
0.75	1.5	0101B577	MD800-2-4T3R4S	3.4	4.6		
1.5	2.2	0101B579	MD800-2-4T4R8S	4.8	5.4		
2.2	3.7	0101B580	MD800-2-4T5R5S	5.5	9		
3.7	5.5	0101B554	MD800-2-4T9R5S	9.5	13		
200 V, DC supply voltage: 270-360 VDC							
0.2	0.4	0101BA86	MD800-2-2T1R7	1.7	1.9	No	
0.4	0.75	0101BA85	MD800-2-2T3	3	3.5		
0.75	1.5	0101BA84	MD800-2-2T5	5	8		
1.5	2.2	0101BA79	MD800-2-2T8	8	9.6		
2.2	3.7	0101BA80	MD800-2-2T11	11	17.6		
0.2	0.4	0101BA83	MD800-2-2T1R7S	1.7	1.9		Yes
0.4	0.75	0101B585	MD800-2-2T3S	3	3.5		
0.75	1.5	0101BD18	MD800-2-2T5S	5	8		
1.5	2.2	0101BD19	MD800-2-2T8S	8	9.6		
2.2	3.7	0101BA87	MD800-2-2T11S	11	17.6		

### Rectifier units

Power (kW)		Part number	Model	Built-in dynamic braking
HD	ND			
3 ph 400 VAC input				
3.7	5.5	0101B573	MD800-0-4T12	No
7.5	11	0101B572	MD800-0-4T22	
15	18.5	0101B571	MD800-0-4T41	
3.7	5.5	0101AK34	MD800-0-4T12B	Yes
7.5	11	01019507	MD800-0-4T22B	
15	18.5	0101AH51	MD800-0-4T41B	
1 ph 200 VAC input				
2.2	3	0101BA52	MD800-0-2S24	No
3.7	4.4	0101B602	MD800-0-2S40	
2.2	3	0101BA53	MD800-0-2S24B	Yes
3.7	4.4	0101B603	MD800-0-2S40B	
3 ph 200 VAC Input				
3.7	5.5	0101C563	MD800-0-2T22B	Yes
7.5	11	0101C562	MD800-0-2T41B	

### Accessories

Part number	Model	Description
01040124	IO-M1	I/O expansion card: 8 DI, 8 DO, 2 AI
01040123	IO-R1	Relay expansion card: 8 relays with normally open contact
01040122	IO-R2	Relay expansion card: 4 relays with changeover contact
01040121	SI-PN	PROFINET communication card
01040120	SI-ECAT	EtherCAT communication card
01040238	SI-EN	Ethernet/IP communication card
In development	SI-EM	Modbus TCP communication card
01040028/20	SOP-20	Remote LCD keypad (inc. 3 m cable)
01040175	MD800-PBJ100M-W1	Rectifier unit cable support bracket
01040176	MD800-PBJ50M-W1	Single or dual drive unit cable support bracket
01040169	MD800-AZB1	Mounting plate for easy assembly of an MD800 set in the electrical panel

\*3 ph input reactors available on request (3-4% impedance)

### EMC Filters

Category	Filter model	Matched rectifier model
EMC filters (To achieve C2 level)	FIL800-4T-045	MD800-0-4T12*
		MD800-0-4T22*
	FIL800-2S-045	MD800-0-4T41*
		MD800-0-2S24*
		MD800-0-2S40*

### INTERNATIONAL OFFICES

**Hong Kong SAR**  
International Export Office  
Tel: +852 2751 6080  
info@inovance.eu

For other country distributors, contact the Hong Kong office.

**Inovance Technology Companies**  
Shenzhen Inovance Technology Co. Ltd.  
Suzhou Inovance Technology Co. Ltd.

### INTERNATIONAL EUROPEAN OFFICES

**Germany-Stuttgart**  
Tel: +49 (0) 7144 8990  
sales.de@inovance.eu

**Italy-Milano**  
Tel: +39 (0) 2268 22318  
sales.it@inovance.eu

**France-Bordeaux**  
Tel: +33 (0) 5594 01050  
sales.fr@inovance.eu

**Spain-Barcelona**  
Tel: +34 93 504 94 48  
sales.es@inovance.eu

**Turkey-Istanbul**  
Tel: +90 (216) 466 7600  
sales.tr@inovance.eu

**South Korea-Seoul**  
Tel: +82 2 3489 8850  
sales.kr@inovance.eu

### INDIAN OFFICES

**Head Office Chennai** Tel: +91 (0) 44 4380 0201

**Ahmedabad** Tel: +91 (0) 79 4003 4274

**Mumbai** Tel: +91 (0) 22 4971 5883

**Noida** Tel: +91 (0) 120 404 3522

**Hyderabad** Tel: +91 (0) 40 4951 6431

**Sales Network** in Kolkata, Bengaluru, Pune, Coimbatore, Visakhapatnam, Vadodara, Jaipur  
info@inovance.ind.in